




ENERG
енергия · ενεργεια



tecalor

TTL 9.5 AC



55 °C

35 °C



A⁺⁺

A⁺⁺



55 dB

■ 16

■ 11

■ 8

kW

■ 15

■ 10

■ 8

kW



2019

811/2013

		TTL 9.5 AC
		190896
Manufacturer		tecalor
Space heating energy efficiency class under average climate conditions, medium-temperature applications		A++
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A++
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	11
Rated heating output under average climate conditions for low-temperature applications (P rated)	kW	10
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s)	%	125
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	159
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	7377
Annual energy consumption under average climate conditions for low-temperature applications (QHE)	kWh/a	5265
Option for operation only at off-peak times		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	16
Rated heating output under colder climate conditions for low-temperature applications (P rated)	kW	15
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	8
Rated heating output under warmer climate conditions for low-temperature applications (P rated)	kW	8
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s)	%	112
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications (η_s)	%	133
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s)	%	128
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)	%	187
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	13625
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)	kWh/a	10540
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	3314
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)	kWh/a	2218
Sound power level, outdoor	dB(A)	55




ENERG
енергия · ενέργεια



tecalor

TTL 9.5 AC



A⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺⁺

A⁺

A

B

C

D

E

F

G

+



+



+



+



Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		TTL 9.5 AC
		190896
Manufacturer		tecalor
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	159
Temperature control class		VI
Contribution of temperature control to space heating energy efficiency	%	4
Space heating energy efficiency of package under average climate conditions	%	129
Space heating energy efficiency of package under colder climate conditions	%	116
Space heating energy efficiency of package under warmer climate conditions	%	132
Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions	%	13
Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions	%	3
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A++
Space heating energy efficiency class of package under average climate conditions		A++

Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		TTL 9.5 AC
		190896
Manufacturer		tecalor
Heat source		Außenluft
Low temperature heat pump		-
With auxiliary heater		x
Combination heater with heat pump		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	16
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	11
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	8
Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	9,7
Tj = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	10,1
Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	7,6
Tj = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	7,8
Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	8,1
Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	8,6
Tj = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	8,4
Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	8,0
Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	9,1
Tj = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	9,1
Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	9,0
Tj = dual mode temperature under colder climate conditions (Pdh)	kW	9,7
Tj = dual mode temperature under average climate conditions (Pdh)	kW	10,1
Tj = dual mode temperature under warmer climate conditions (Pdh)	kW	8,1
Tj = operating temperature limit under colder climate conditions (Pdh)	kW	7,5
Tj = operating temperature limit under average climate conditions (Pdh)	kW	9,4
Tj = operating temperature limit under warmer climate conditions (Pdh)	kW	8,1
Dual mode temperature under colder climate conditions (Tbiv)	°C	-7
Dual mode temperature under average climate conditions (Tbiv)	°C	-7
Dual mode temperature under warmer climate conditions (Tbiv)	°C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (ηs)	%	112
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (ηs)	%	125
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (ηs)	%	128
Tj = -7 °C COP, partial load range under colder climate conditions (COPd)		2,82
Tj = -7 °C COP, partial load range under average climate conditions (COPd)		2,56
Tj = 2 °C COP, partial load range under colder climate conditions (COPd)		3,55
Tj = 2 °C COP, partial load range under average climate conditions (COPd)		3,31
Tj = 2 °C COP, partial load range under warmer climate conditions (COPd)		2,78
Tj = 7 °C COP, partial load range under colder climate conditions (COPd)		4,46
Tj = 7 °C COP, partial load range under average climate conditions (COPd)		4,14
Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)		3,40

Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		4,88
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		474,00
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		4,48
Tj = dual mode temperature under colder climate conditions (COPd)		2,82
Tj = dual mode temperature under average climate conditions (COPd)		2,56
Tj = dual mode temperature under warmer climate conditions (COPd)		2,78
Tj = operating temperature limit under colder climate conditions (COPd)		1,85
Tj = operating temperature limit under average climate conditions (COPd)		2,26
Tj = operating temperature limit under warmer climate conditions (COPd)		2,78
Operating temperature limit under colder climate conditions (TOL)	°C	-20
Operating temperature limit under average climate conditions (TOL)	°C	-10
Operating temperature limit under warmer climate conditions (TOL)	°C	2
Operating temperature limit of heating water under colder climate conditions (WTOL)	°C	65
Operating temperature limit of heating water under average climate conditions (WTOL)	°C	65
Operating temperature limit of heating water under warmer climate conditions (WTOL)	°C	65
Power consumption, off-mode (Poff)	W	10
Power consumption, thermostat off-mode (PTO)	W	10
Power consumption, standby state (PSB)	W	10
Power consumption, operating state, with crankcase heating (PCK)	W	38
Rated heating output of auxiliary heater under colder climate conditions (PSUP)	kW	15,9
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	2,0
Type of energy supply, auxiliary heater		elektrisch
Output control		veränderlich
Sound power level, outdoor	dB(A)	55
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	13625
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	7377
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	3314
Flow rate on heat source side	m³/h	4000