



ENERGY


tecalor

TTF 10



55 °C

35 °C



48 dB



■ 12

■ 9

■ 9

kW

■ 13

■ 10

■ 10

kW



2019

811/2013

		TTF 10
		190336
Manufacturer		tecalor
Space heating energy efficiency class under average climate conditions, medium-temperature applications		A++
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	9
Rated heating output under average climate conditions for low-temperature applications (P rated)	kW	10
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s)	%	137
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	216
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	5176
Annual energy consumption under average climate conditions for low-temperature applications (QHE)	kWh/a	3799
Sound power level, indoor	dB(A)	48
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	12
Rated heating output under colder climate conditions for low-temperature applications (P rated)	kW	13
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	9
Rated heating output under warmer climate conditions for low-temperature applications (P rated)	kW	10
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s)	%	144
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications (η_s)	%	224
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s)	%	136
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)	%	215
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	7549
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)	kWh/a	5457
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	3367
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)	kWh/a	2466



ENERGY

tecator

TTF 10



A⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺⁺

A⁺

A

B

C

D

E

F

G

+



+



+



+



Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		TTF 10
		190336
Manufacturer		tecalor
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	216
Temperature control class		VII
Contribution of temperature control to space heating energy efficiency	%	4
Space heating energy efficiency of package under average climate conditions	%	141
Space heating energy efficiency of package under colder climate conditions	%	148
Space heating energy efficiency of package under warmer climate conditions	%	140
Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions	%	7
Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions	%	1
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Space heating energy efficiency class of package under average climate conditions		A++

Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		TTF 10
		190336
Manufacturer		tecalor
Heat source		Sole
With auxiliary heater		x
Combination heater with heat pump		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	12
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	9
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	9
Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	9,6
Tj = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	9,2
Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	9,9
Tj = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	9,6
Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	9,1
Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	10,1
Tj = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	9,9
Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	9,5
Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	10,3
Tj = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	10,1
Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	10,0
Tj = dual mode temperature under colder climate conditions (Pdh)	kW	9,5
Tj = dual mode temperature under average climate conditions (Pdh)	kW	9,1
Tj = dual mode temperature under warmer climate conditions (Pdh)	kW	9,1
Tj = operating temperature limit under colder climate conditions (Pdh)	kW	9,1
Tj = operating temperature limit under average climate conditions (Pdh)	kW	9,1
Tj = operating temperature limit under warmer climate conditions (Pdh)	kW	9,1
For air source heat pumps: Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	9,1
Dual mode temperature under colder climate conditions (Tbiv)	°C	-15
Dual mode temperature under average climate conditions (Tbiv)	°C	-10
Dual mode temperature under warmer climate conditions (Tbiv)	°C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (ηs)	%	144
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (ηs)	%	137
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (ηs)	%	136
Tj = -7 °C COP, partial load range under colder climate conditions (COPd)		3,55
Tj = -7 °C COP, partial load range under average climate conditions (COPd)		2,97
Tj = 2 °C COP, partial load range under colder climate conditions (COPd)		4,03
Tj = 2 °C COP, partial load range under average climate conditions (COPd)		3,56
Tj = 2 °C COP, partial load range under warmer climate conditions (COPd)		2,83
Tj = 7 °C COP, partial load range under colder climate conditions (COPd)		4,48
Tj = 7 °C COP, partial load range under average climate conditions (COPd)		4,03
Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)		3,28

Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		4,87
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		46,00
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		4,21
Tj = dual mode temperature under colder climate conditions (COPd)		3,30
Tj = dual mode temperature under average climate conditions (COPd)		2,83
Tj = dual mode temperature under warmer climate conditions (COPd)		2,83
Tj = operating temperature limit under colder climate conditions (COPd)		2,83
Tj = operating temperature limit under average climate conditions (COPd)		2,83
Tj = operating temperature limit under warmer climate conditions (COPd)		2,83
For air source heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd)		2,83
Operating temperature limit of heating water under average climate conditions (WTOL)	°C	65
Power consumption, off-mode (Poff)	W	0
Power consumption, thermostat off-mode (PTO)	W	84
Power consumption, standby state (PSB)	W	9
Power consumption, operating state, with crankcase heating (PCK)	W	0
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	0,0
Type of energy supply, auxiliary heater		elektrisch
Output control		fest
Sound power level, indoor	dB(A)	48
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	7549
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	5176
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	3367
Flow rate on heat source side	m³/h	261