



ENERGY

tecalor

TTF 57.6 l topline



55 °C

35 °C



A+++

A+++



44 dB



■ 56

■ **56**

■ 56

kW

■ 58

■ **58**

■ 58

kW



2019

811/2013

		TTF 57.6 l topline
		191014
Manufacturer		tecalor
Space heating energy efficiency class under average climate conditions, medium-temperature applications		A+++
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	56
Rated heating output under average climate conditions for low-temperature applications (P rated)	kW	58
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s)	%	163
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	205
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	27150
Annual energy consumption under average climate conditions for low-temperature applications (QHE)	kWh/a	22720
Sound power level, indoor	dB(A)	44
Option for operation only at off-peak times		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	56
Rated heating output under colder climate conditions for low-temperature applications (P rated)	kW	58
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	56
Rated heating output under warmer climate conditions for low-temperature applications (P rated)	kW	58
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s)	%	170
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications (η_s)	%	213
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s)	%	165
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)	%	207
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	30994
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)	kWh/a	26039
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	17310
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)	kWh/a	14551



ENERGY

TTF 57.6 l topline

tecalor



A⁺⁺⁺

A⁺⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺

A

B

C

D

E

F

G

+



+



+



+



Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		TTF 57.6 I topline
		191014
Manufacturer		tecalor
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	205
Temperature control class		II
Contribution of temperature control to space heating energy efficiency	%	2
Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions	%	5
Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions	%	2
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Space heating energy efficiency class of package under average climate conditions		A+++

Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		TTF 57.6 I topline
		191014
Manufacturer		tecalor
Heat source		Sole
Low temperature heat pump		-
With auxiliary heater		-
Combination heater with heat pump		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	56
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	56
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	56
Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	34,0
Tj = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	49,6
Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	20,7
Tj = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	30,2
Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	56,1
Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	15,7
Tj = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	19,4
Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	36,1
Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	15,8
Tj = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	15,7
Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	16,0
Tj = dual mode temperature under colder climate conditions (Pdh)	kW	56,1
Tj = dual mode temperature under average climate conditions (Pdh)	kW	56,1
Tj = dual mode temperature under warmer climate conditions (Pdh)	kW	56,1
Tj = operating temperature limit under colder climate conditions (Pdh)	kW	56,1
Tj = operating temperature limit under average climate conditions (Pdh)	kW	56,1
Tj = operating temperature limit under warmer climate conditions (Pdh)	kW	56,1
Dual mode temperature under colder climate conditions (Tbiv)	°C	-22
Dual mode temperature under average climate conditions (Tbiv)	°C	-10
Dual mode temperature under warmer climate conditions (Tbiv)	°C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (ηs)	%	170
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (ηs)	%	163
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (ηs)	%	165
Tj = -7 °C COP, partial load range under colder climate conditions (COPd)		3,99
Tj = -7 °C COP, partial load range under average climate conditions (COPd)		3,09
Tj = 2 °C COP, partial load range under colder climate conditions (COPd)		4,95
Tj = 2 °C COP, partial load range under average climate conditions (COPd)		4,25
Tj = 2 °C COP, partial load range under warmer climate conditions (COPd)		2,85
Tj = 7 °C COP, partial load range under colder climate conditions (COPd)		5,35
Tj = 7 °C COP, partial load range under average climate conditions (COPd)		5,05
Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)		3,77

Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		5,39
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		5,29
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		5,23
Tj = dual mode temperature under colder climate conditions (COPd)		2,85
Tj = dual mode temperature under average climate conditions (COPd)		2,85
Tj = dual mode temperature under warmer climate conditions (COPd)		2,85
Tj = operating temperature limit under colder climate conditions (COPd)		2,85
Tj = operating temperature limit under average climate conditions (COPd)		2,85
Tj = operating temperature limit under warmer climate conditions (COPd)		2,85
Power consumption, off-mode (Poff)	W	12
Power consumption, thermostat off-mode (PTO)	W	12
Power consumption, standby state (PSB)	W	12
Power consumption, operating state, with crankcase heating (PCK)	W	0
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	0,0
Rated heating output of auxiliary heater under warmer climate conditions (PSUP)	kW	0,0
Type of energy supply, auxiliary heater		elektrisch
Output control		veränderlich
Sound power level, indoor	dB(A)	44
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	30994
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	27150
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	17310